

DURACELL®

TECHNICAL DATA SHEET

Type no.	DE 70 AGM
Article no.	016570010801
EAN/GTIN no.	9005753086098
Application	Starter battery start-stop
Electrical data	
Rated voltage	12V
Rated capacity	70 Ah (K20)
Cold start current	760 A (EN)
Dimensions and weights	
Box	L3
Length max.	278mm
Width max.	175mm
Box height max.	190mm
Total height max.	190mm
Battery weight	Ca. 21,0 kg (+/- 5 %)
Electrolyte density	Approx. 1,32 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	64
Pallet ID	Euro pallet
Items per layer	16
Features	
Base hold-down	B13
Layout	0
Terminal	1
Separator	AGM separator
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W5 - C2 - V3 - M3 (E4)
Maintenance 1)	
Water consumption	W5
Refill water	Absolutely maintenance-free
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/20 of the rated capacity
Charging voltage 2)	max. 14,8 V



1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

